



SLIM LINE

LIQUID MANURE SPREADER



COMMITTED TO QUALITY YOU CAN DEPEND ON!

- 10 Year **WARRANTY** Against Tank Rust Out
- 5 Year Axle And Undercarriage **WARRANTY**
- Adjustable Axle For Best Weight
- Prime High Carbon Heavy Gauge Steel Tank
- Fully Lined Inside Against Rust
- All Seams Welded Inside And Out
- Flanged Ends & Full Baffle For Strength
- Parts Book And Owners Manual Supplied
- High Strength Steel
- Constant Velocity P.T.O.
- Handling Manure **SINCE 1960**
- **CUSTOM BUILT** For Special Applications



TIRE OPTIONS

- 28L X 26 Turf Tires
- 35.5L X 32 Radial Tires
- 30.5L X 32 Radial Tires
- More Options with Axles Custom Built To Suit All Tire Options

Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2,
Alma, Ontario Canada N0B 1A0

www.huskyfarm.ca

Phone (519) 846 - 5329 Fax (519) 846 - 9378

1-800-349-1122

	Tandem	Tandem	Tri Axle	Tandem	Tri Axle
Litres	18000	24500	27500	27500	30200
U.S Gallons	5000	6500	7200	7200	8000
Can Gallon	4000	5400	6050	6050	6500
Tractor Size	150	200	230	230	230

All H.P And Sizes Are Approximate



OPTIONS

- Spreading pattern up to 60 ft
- Discharge height 135" optional 4 ft Pipe Down The Back
- Walking tandem Axle
- Steering Tri Axle
- Hydraulic drive
- 1000 RPM or 540 RPM
- PTO Constant velocity, shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T
- Tank ends Flanged and reinforced
- Light kit (brake & tail) Standard
- Butterfly Lid
- Clean Out 8"
- Camel Hump
- Sight Gauge
- Slide Lid
- In tank Agitation
- Flow Control Valves
- Anti Syphon
- Top Coat Urethane acid resistant
- Epoxy Primer Inside Coating Aluminized epoxy acid resistant
- 6" or 8" Discharge
- Unloading speed 8" discharge up to 3600 gallon per minute adjustable
- Unloading speed 6" discharge up to 2400 gallon per minute adjustable



FULL BAFFLES IN EVERY TANK



INJECTORS



GALVANIZING



SWING AWAY FAN



DEALER