



# Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0  
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122  
[husky@huskyfarm.ca](mailto:husky@huskyfarm.ca) [www.huskyfarm.ca](http://www.huskyfarm.ca)



## 12000L Galvanized

	<b>21.5L x 16.1, 10 Ply Tandem</b>	<b>28L x 26, 12 Ply Single Axle</b>
Compaction	1844 sq. in. on ground	1872 sq. in. on ground @ 24 PSI
Overall height	111" (2819 mm)	109" (2768 mm)
Overall width	122.5" (3111 mm)	144" (3657 mm)
Tire pressure	35 lbs	24 lbs
Tire type	Rib implement type	Knobby turf type
Axle capacity	64000 lbs	37000 lbs
Axle width flange to flange	100"	113.87", 2892 mm straight axle
Empty	6,730 lbs (3,059 kg)	5,900 lbs (2,676 kg)
Loaded	31,720 lbs (14,418 kg)	35,900 lbs (15,876 kg)

86" (2184 mm) X 62" (1154 mm) X 14 ft (4.27 m)  
 Flanged and reinforced ends welded inside and out  
 3/16" (4.5 mm) shell  
 1 full baffle  
 Tongue is 73 inches long 4"x 8" boxed tubing 1/4" material  
 Single or double, height adjustable and weight adjustable, 5000 lbs Tongue jack  
 540 PTO Unloading pump 4 blade 10 bolt Hub, 11.1/4" bolt circle, 8 5/8" pilot hole, hub greaseable, 4" spindle C1045  
 5 year unconditional axle warranty (non commercial)

**Standard Features**  
 Bearings Tapered roller  
 Seals Double lip grease purge able  
 PTO Constant velocity shear protected 1 3/8 6 T,  
 1 3/8 21T, 1 3/4 20T  
 Size of discharge 6"  
 Spreading pattern Up to 60 ft, 18 m  
 Discharge height 106", 2692 mm optional 4 ft  
 Unloading speed 6" discharge Up to 2400 gallon  
 per minute adjustable  
 Hot Dip Galvanized  
 Axle warranty 5 year unconditional  
 Light kit ( brake & tail) Standard  
 Unloading pump 4 blade fan type  
 RPM 540  
 Draw bar weight Adjustable  
 Walking tandem Axle  
 Seams welded solid inside

**Options For Your Husky Tank**  
 Hydraulic drive  
 Butterfly Lid  
 Clean Out  
 Camels Hump  
 Pipe Down the back  
 Sight Gage  
 Swing Away Fan  
 Slide Lid  
 Square Man Hole  
 In tank Agitation  
 Valves  
 1000 RPM Unload  
 Low Spread  
 Single Hitch