



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



12000L Vacuum

21.5L x 16.1, 10 Ply Tandem

Compaction	1844 sq. in. on ground
Overall height	111" (2819 mm)
Overall width	122.5" (3111 mm)
Tire pressure	35 lbs
Tire type	Rib implement type
Axle capacity	64000 lbs
Axle width flange to flange	100"
Empty	6,730 lbs (3,059 kg)
Loaded	31,720 lbs (14,418 kg)

28L x 26, 12 Ply Single Axle

Compaction	1872 sq. in. on ground @ 24 PSI
Overall height	109" (2768 mm)
Overall width	144" (3657 mm)
Tire pressure	24 lbs
Tire type	Knobby turf type
Axle capacity	37000 lbs
Axle width flange to flange	113.87", 2892 mm straight axle
Empty	5,900 lbs (2,676 kg)
Loaded	35,900 lbs (15,876 kg)

86" (2184 mm) X 62" (1154 mm) X 14 ft (4.27 m)
 Flanged and reinforced ends welded inside and out
 3/16" (4.5 mm) shell
 1 full baffle
 U shaped sills, 1/4", Total contact tank to sill area 6 square ft
 Tongue is 73 inches long 4"x 8" boxed tubing 1/4" material
 Single or double, height adjustable and weight adjustable, 5000 lbs Tongue jack
 Constant velocity PTO shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T
 10 bolt Hub, 11.1/4" bolt circle, 8 5/8" pilot hole, hub greaseable, 4" spindle C1045
 1/4" (6.35 mm) tank shell high strength steel
 1/4" Tank ends flanged and dished
 Full Baffle welded inside and out
 Sight gauge standard front drivers side
 Walking tandem axle 5 year warranty
 U shaped sills with full length support
 Light kit (brake & tail) standard
 Tongue 73 inches 4"x 8" x 1/4 tubing
 24" rear access hatch , 6" hydraulic discharge
 6" manual side valve
 15 feet 6" suction hose with Bauer ends
 Primary and secondary moisture trap with 6" stainless ball
 3" (75 MM) air intake and outlet lines
 10 Year rust out warranty
 High speed vacuum pumps air cooled
 High heat vanes / air cooled / 540/ 1000
 C V PTO standard, hydraulic drive optional

Options For Your Husky Tank

- Hydraulic lid
- Vacuum pumps 6 sizes to choose from
- 30 " Domed manhole
- Hydraulic drive
- Butterfly Lid
- Valves
- 1000 RPM Unload
- Single Hitch

PAINT

The tank is steam cleaned with phosphate blown dry and heated
 Primed with an epoxy primer and finished with two coats of Urethane
 Inside is cleaned and painted with aluminized epoxy



All Figures Are Approximate, Limited Warranty (3Months For Custom Operators), No Warranty On Sand Bedding.
 For Full Details and Exact Figures, Please Confirm With Husky. 1-800-349-1122