



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
 Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



HUSKY 12000 ELITE

3000 US Gal., 2500 CDN Gal., 12000 Litres



21.5L x 16.1, 10 Ply Tandem

Compaction	1844 sq. in. on ground
Overall height	111" (2819 mm)
Overall width	122.5" (3111 mm)
Tire pressure	35 lbs
Tire type	Rib implement type
Axle capacity	64000 lbs
Axle width flange to flange	100"
Empty	6,730 lbs (3,059 kg)
Loaded	31,720 lbs (14,418 kg)

28L x 26, 12 Ply Single Axle

Compaction	1872 sq. in. on ground @ 24 PSI
Overall height	109" (2768 mm)
Overall width	144" (3657 mm)
Tire pressure	24 lbs
Tire type	Knobby turf type
Axle capacity	37000 lbs
Axle width flange to flange	113.87", 2892 mm straight axle
Empty	5,900 lbs (2,676 kg)
Loaded	35,900 lbs (15,876 kg)

86" (2184 mm) X 62" (1154 mm) X 14 ft (4.27 m)
 Flanged and reinforced ends welded inside and out
 3/16" (4.5 mm) shell, 1 full baffle
 U shaped sills, 1/4", Total contact tank to sill area 6 square ft
 Tongue is 73 inches long 4"x 8" boxed tubing 1/4" material
 Double height adjustable hitch, weight adjustable, 5000 lbs Tongue jack
 10 bolt Hub, 11.1/4" bolt circle, 8 5/8" pilot hole, hub greaseable, 4" spindle C1045
 5 year unconditional axle warranty (non commercial)

Options For Your Husky Tank

- Hydraulic drive
- Butterfly Lid
- Clean Out
- Camels Hump
- Pipe Down the back
- Sight Gage
- Swing Away Fan
- Slide Lid
- In tank Agitation
- Valves
- 1000 RPM Unload
- Low Spread
- Single Hitch



Standard Features

- Bearings Tapered roller
- Seals Double lip grease purge able
- PTO Constant velocity shear protected 1 3/8 6 T, 1 3/8 21T, 1 3/4 20T
- Size of discharge 6"
- Spreading pattern Up to 60 ft, 18 m
- Discharge height 106", 2692 mm optional 4 ft
- Unloading speed 6" discharge Up to 2400 gallon per minute adjustable
- Painting preparation Steamed with phosphate
- Paint primed Epoxy
- Paint finish coat Urethane
- Inside coating Aluminized epoxy
- Axle warranty 5 year unconditional
- Light kit (brake & tail) Standard
- Unloading pump 4 blade fan type RPM 540
- Draw bar weight Adjustable
- Walking tandem Axle
- Seams welded solid inside
- Full Baffle In All Tanks

All Figures Are Approximate, Limited Warranty (3Months For Custom Operators), No Warranty On Sand Bedding.
 For Full Details and Exact Figures, Please Confirm With Husky. 1-800-349-1122