



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



HUSKY 15000 ELITE

4000 US Gal., 3300 CDN Gal., 15000 Litres

21.5L x 16.1, 14 Ply

Compaction	1844 sq. in. on ground @ 35 PSI
Tire type	Rib implement type
Overall height	111 " (2881 mm)
Overall width	122" (3740 mm)
Discharge height	125" inches optional 4 ft
Empty	7,288 lbs (3,312 kg)
Loaded	40,608 lbs (18,454 kg)
Tank width	90" (2286 mm)
Tank height	70" (1778 mm)
Tank length	15 ft (4.57 m)
Tank ends	Flanged and reinforced
Tank shell thickness	3/16" (4.5 mm)
Number of baffles	1
Tongue jack	5000 LB
Draw bar weight	Adjustable
Axle type	Walking tandem
Axle capacity	64000 lbs (29350 kg)
Axle spindle size & material	4" C1045
Hitch	Single or double, height adjustable
Hub bolt pattern	10 bolt, 11.1/4" bolt circle, 8 5/8" pilot hole, hub greaseable
Axle width flange to flange	Drop axle 120"
Axle warranty	5 year unconditional (non commercial)

28L x 26, 12 Ply

3744 sq. in. on ground @ 24 PSI
Knobby turf type
113.5 " (2881 mm)
149.5" (3797 mm)
127" optional 4 ft
9,260 lbs (4,209 kg)
42,580 lbs (19,354 kg)



Options For Your Husky Tank

- 8" Discharge Unloading Up to 3600 gallon per minute adjustable
- Hydraulic drive
- Butterfly Lid
- Clean Out
- Camels Hump
- Pipe Down the back
- Sight Gage
- Swing Away Fan
- Slide Lid
- Square Man Hole
- Cut Outs
- High Speed Tires
- Steering
- In tank Agitation
- Valves
- 1000 RPM Unload
- Low Spread
- Single Hitch

Standard Features

- Bearings Tapered roller
- Seals Double lip grease purge able
- PTO Constant velocity shear protected 1 3/8 6 T, 1 3/8 21T, 1 3/4 20T
- Size of discharge 6"
- Spreading pattern Up to 60 ft, 18 m
- Discharge height 106", 2692 mm optional 4 ft
- Unloading speed 6" discharge Up to 2400 gallon per minute adjustable
- Painting preparation Steamed with phosphate
- Paint primed Epoxy
- Paint finish coat Urethane
- Inside coating Aluminized epoxy
- Axle warranty 5 year unconditional
- Light kit (brake & tail) Standard
- Unloading pump 4 blade fan type RPM 540
- Draw bar weight Adjustable
- Walking tandem Axle
- Seams welded solid inside

All Figures Are Approximate, Limited Warranty (3Months For Custom Operators), No Warranty On Sand Bedding.
For Full Details and Exact Figures, Please Confirm With Husky. 1-800-349-1122