



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
 Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



Special Order Only

HUSKY 23000 ELITE

Special Order Only

6000 US Gal., 5000 CDN Gal., 23000 Litres

28L x 26, 12 Ply **30.5L x 32, 12 Ply**

Compaction	3744 sq. in. on ground	4508 sq. in. on ground w/ 3" penetration
Overall height	120"	125"
Overall width	163"	163"
Discharge height	136", optional 4 ft	141" optional 4 ft
Empty	16,537 lbs (7,516 kg)	16,960 lbs (7,693 kg)
Loaded	66,517 lbs (30,235 kg)	66,940 lbs (30,364 kg)
Tire pressure	24 lbs	
Tire type	Turf type, knobby tread	
Tank width	100"	
Tank height	78"	
Tank length	19.25 ft	
Tank ends	Flanged and reinforced	
Tank shell thickness	1/4"	
Number of baffles	2 full baffles	
Tongue type and thickness	Rectangular tubing 3/8" material	
Hitch	Single or optional double hitch	
Tongue jack	8000 lbs	
Axle weight (less tires)	4432 lbs, 2010 kg	
Axle capacity	100,000 lbs, 45,360 kg	
Axle warranty	5 year (non commercial)	
Light kit (brake & tail)	Standard	
Axle spindle size & material	5 1/2" stress proof slid in 6 1/2" sleeve	
Hub bolt pattern	10 bolt, 13.19" bolt circle hub greaseable	



Standard Features

Bearings Tapered roller
 Seals Double lip grease purge able
 PTO Constant velocity shear protected 1 3/8 6
 T, 1 3/8 21T, 1 3/4 20T
 Size of discharge 6"
 Spreading pattern Up to 60 ft, 18 m
 Discharge height 106", 2692 mm optional 4 ft
 Unloading speed 6" discharge Up to 2400
 gallon per minute adjustable
 Painting preparation Steamed with phosphate
 Paint primed Epoxy
 Paint finish coat Urethane
 Inside coating Aluminized epoxy
 Axle warranty 5 year unconditional
 Light kit (brake & tail) Standard
 Unloading pump 4 blade fan type
 Draw bar weight Adjustable
 Walking tandem Axle
 Seams welded solid inside
 U shape, 1/4" Sill
 9.75 square ft Padding to tank contact
 4"x 8" boxed tubing 1/4" material on tongue
 73" Tongue



Options For Your Husky Tank

8" Discharge Unloading speed Up to
 3600 gallon per minute adjustable
 Hydraulic drive
 Butterfly Lid
 Clean Out
 Camels Hump
 Pipe Down the back
 Sight Gage
 Swing Away Fan
 Slide Lid
 Square Man Hole
 In tank Agitation
 Valves
 1000 RPM Unload
 Low Spread
 Single Hitch

All Figures Are Approximate, Limited Warranty (3Months For Custom Operators), No Warranty On Sand Bedding.
 For Full Details and Exact Figures, Please Confirm With Husky. 1-800-349-1122