



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
 Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



24500L Tri Axle



30.5L x 32, 12 Ply, Optional 35.5 x 32

Compaction	4508 sq. in. on ground
Tire pressure	26/30 lbs
Tire type	Turf type, knobby tread
Tank ends	Flanged and reinforced
Tank shell thickness	1/4" high strength steel
Number of baffles	2 full baffles
Inside coating	Aluminized epoxy
Light kit (brake & tail)	Standard
Seams welded solid inside	Yes
Sill style & thickness	U shape, 1/2" material, 3/4" over axle
Padding - sills to tank contact	12 square ft
Tongue type and thickness	4" x 8" rectangular tubing 3/8" material
Hitch	Single or optional double hitch
Tongue jack	8000 lbs
Unloading pump	Fan type with high efficiency blades
RPM	1000, optional 540 RPM
Hydraulic drive	Optional
Bearings	Timken taper, grease filled chamber
Seals	Double seals, purgeable
PTO	Constant velocity, shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T
Hydraulic drive	Optional
Size of discharge	6", 8" optional
Unloading speed 6" discharge	Up to 2400 gallon per minute adjustable
Spreading pattern	Up to 60 ft
Discharge height	135" optional 4 ft
Axle type	Walking tandem
Axle weight (less tires)	4432 lbs, 2009 kg
Axle capacity	
Axle warranty	5 year (non commercial)
Hub bolt pattern	10 bolt, 13.19" bolt circle, 11 1/16 pilot hole, hub greaseable
Painting preparation	Steamed with phosphate Paint
Primer	Aluminized epoxy acid resistant
Paint finish coat	Urethane acid resistant
Empty	24,000 lbs
Loaded	94,000 lbs



Overall Height	3672mm 144.5"
Overall Width	3404mm 134"
Overall Length	10545mm 415" 34.5ft (With Inside Agitation)
Tank Width	2565mm 101"
Tank Height	1920mm 75.5"
Tank Length	7363mm 290" 24ft
Number Of Baffles	3
Sill Out Side Dimension	1372mm 54"
Tongue Length	1905mm 75"



Options For Your Husky Tank
8" Discharge Unloading speed
Up to 3600 gallon per minute adjustable
Hydraulic drive
Butterfly Lid
Clean Out
Camels Hump
Pipe Down the back
Sight Gage
In tank Agitation
Valves
1000 RPM Unload
Low Spread
Single Hitch

All Figures Are Approximate, Limited Warranty (3Months For Custom Operators), No Warranty On Sand Bedding.
 For Full Details and Exact Figures, Please Confirm With Husky. 1-800-349-1122